

Technical drawing of a rectangular plate with dimensions and hole specifications. The plate has a width of 30 and a height of 60. It features a central rectangular hole with a width of 25 and a height of 10. The hole is positioned 25 units from the top and bottom edges and 5 units from the left and right edges. The plate has four holes: two on the top edge (2x Ø14) and two on the bottom edge (2x Ø20). The distance between the centers of the top holes is 30, and the distance between the centers of the bottom holes is 30. The distance from the center of the top hole to the center of the bottom hole is 60. The plate is shown with a dashed line indicating its full width of 30. The text 'staffa Ø8 (L=180)' is present below the drawing.

Technical drawing of a rectangular frame assembly. The drawing shows a central rectangular frame with dimensions 30 (width) and 60 (height). The frame is composed of four vertical bars, each labeled 2Ø14. The top and bottom bars are also labeled 2Ø20. The frame is mounted on a horizontal base, which is labeled 3Ø20. The base is supported by two vertical posts, each labeled 2Ø14. The total height of the assembly is 60. The total width of the assembly is 30. The frame is labeled staffa Ø8 (L=180).

Technical drawing of a rectangular plate with dimensions and hole specifications. The plate has a width of 30 and a height of 60. It features four holes: two at the top corners (3Ø20) and two at the bottom corners (2Ø14). The distance between the centers of the top holes is 1Ø14, and the distance between the centers of the bottom holes is 2Ø14. The distance from the top edge to the center of the top holes is 22, and the distance from the bottom edge to the center of the bottom holes is 25. The distance from the left edge to the center of the left holes is 10, and the distance from the right edge to the center of the right holes is 10. The plate is labeled 'staffa Ø8 (L=180)'.

Diagrammi Momenti Sollecitanti e Resistenti (1cm=50kNm)

The diagram shows the distribution of bending moments (M) in kNm along the length of the structure. The horizontal axis represents the distance in meters (m), with major grid lines at 0, 20.14, 20.30, 20.34, 20.36, 20.38, 20.40, 20.42, 20.44, 20.46, 20.48, 20.50, 20.52, 20.54, 20.56, 20.58, 20.60, 20.62, 20.64, 20.66, 20.68, 20.70, 20.72, 20.74, 20.76, 20.78, 20.80, 20.82, 20.84, 20.86, 20.88, 20.90, 20.92, 20.94, 20.96, 20.98, 21.00, 21.02, 21.04, 21.06, 21.08, 21.10, 21.12, 21.14, 21.16, 21.18, 21.20, 21.22, 21.24, 21.26, 21.28, 21.30, 21.32, 21.34, 21.36, 21.38, 21.40, 21.42, 21.44, 21.46, 21.48, 21.50, 21.52, 21.54, 21.56, 21.58, 21.60, 21.62, 21.64, 21.66, 21.68, 21.70, 21.72, 21.74, 21.76, 21.78, 21.80, 21.82, 21.84, 21.86, 21.88, 21.90, 21.92, 21.94, 21.96, 21.98, 22.00, 22.02, 22.04, 22.06, 22.08, 22.10, 22.12, 22.14, 22.16, 22.18, 22.20, 22.22, 22.24, 22.26, 22.28, 22.30, 22.32, 22.34, 22.36, 22.38, 22.40, 22.42, 22.44, 22.46, 22.48, 22.50, 22.52, 22.54, 22.56, 22.58, 22.60, 22.62, 22.64, 22.66, 22.68, 22.70, 22.72, 22.74, 22.76, 22.78, 22.80, 22.82, 22.84, 22.86, 22.88, 22.90, 22.92, 22.94, 22.96, 22.98, 23.00, 23.02, 23.04, 23.06, 23.08, 23.10, 23.12, 23.14, 23.16, 23.18, 23.20, 23.22, 23.24, 23.26, 23.28, 23.30, 23.32, 23.34, 23.36, 23.38, 23.40, 23.42, 23.44, 23.46, 23.48, 23.50, 23.52, 23.54, 23.56, 23.58, 23.60, 23.62, 23.64, 23.66, 23.68, 23.70, 23.72, 23.74, 23.76, 23.78, 23.80, 23.82, 23.84, 23.86, 23.88, 23.90, 23.92, 23.94, 23.96, 23.98, 24.00, 24.02, 24.04, 24.06, 24.08, 24.10, 24.12, 24.14, 24.16, 24.18, 24.20, 24.22, 24.24, 24.26, 24.28, 24.30, 24.32, 24.34, 24.36, 24.38, 24.40, 24.42, 24.44, 24.46, 24.48, 24.50, 24.52, 24.54, 24.56, 24.58, 24.60, 24.62, 24.64, 24.66, 24.68, 24.70, 24.72, 24.74, 24.76, 24.78, 24.80, 24.82, 24.84, 24.86, 24.88, 24.90, 24.92, 24.94, 24.96, 24.98, 25.00, 25.02, 25.04, 25.06, 25.08, 25.10, 25.12, 25.14, 25.16, 25.18, 25.20, 25.22, 25.24, 25.26, 25.28, 25.30, 25.32, 25.34, 25.36, 25.38, 25.40, 25.42, 25.44, 25.46, 25.48, 25.50, 25.52, 25.54, 25.56, 25.58, 25.60, 25.62, 25.64, 25.66, 25.68, 25.70, 25.72, 25.74, 25.76, 25.78, 25.80, 25.82, 25.84, 25.86, 25.88, 25.90, 25.92, 25.94, 25.96, 25.98, 26.00, 26.02, 26.04, 26.06, 26.08, 26.10, 26.12, 26.14, 26.16, 26.18, 26.20, 26.22, 26.24, 26.26, 26.28, 26.30, 26.32, 26.34, 26.36, 26.38, 26.40, 26.42, 26.44, 26.46, 26.48, 26.50, 26.52, 26.54, 26.56, 26.58, 26.60, 26.62, 26.64, 26.66, 26.68, 26.70, 26.72, 26.74, 26.76, 26.78, 26.80, 26.82, 26.84, 26.86, 26.88, 26.90, 26.92, 26.94, 26.96, 26.98, 27.00, 27.02, 27.04, 27.06, 27.08, 27.10, 27.12, 27.14, 27.16, 27.18, 27.20, 27.22, 27.24, 27.26, 27.28, 27.30, 27.32, 27.34, 27.36, 27.38, 27.40, 27.42, 27.44, 27.46, 27.48, 27.50, 27.52, 27.54, 27.56, 27.58, 27.60, 27.62, 27.64, 27.66, 27.68, 27.70, 27.72, 27.74, 27.76, 27.78, 27.80, 27.82, 27.84, 27.86, 27.88, 27.90, 27.92, 27.94, 27.96, 27.98, 28.00, 28.02, 28.04, 28.06, 28.08, 28.10, 28.12, 28.14, 28.16, 28.18, 28.20, 28.22, 28.24, 28.26, 28.28, 28.30, 28.32, 28.34, 28.36, 28.38, 28.40, 28.42, 28.44, 28.46, 28.48, 28.50, 28.52, 28.54, 28.56, 28.58, 28.60, 28.62, 28.64, 28.66, 28.68, 28.70, 28.72, 28.74, 28.76, 28.78, 28.80, 28.82, 28.84, 28.86, 28.88, 28.90, 28.92, 28.94, 28.96, 28.98, 29.00, 29.02, 29.04, 29.06, 29.08, 29.10, 29.12, 29.14, 29.16, 29.18, 29.20, 29.22, 29.24, 29.26, 29.28, 29.30, 29.32, 29.34, 29.36, 29.38, 29.40, 29.42, 29.44, 29.46, 29.48, 29.50, 29.52, 29.54, 29.56, 29.58, 29.60, 29.62, 29.64, 29.66, 29.68, 29.70, 29.72, 29.74, 29.76, 29.78, 29.80, 29.82, 29.84, 29.86, 29.88, 29.90, 29.92, 29.94, 29.96, 29.98, 30.00, 30.02, 30.04, 30.06, 30.08, 30.10, 30.12, 30.14, 30.16, 30.18, 30.20, 30.22, 30.24, 30.26, 30.28, 30.30, 30.32, 30.34, 30.36, 30.38, 30.40, 30.42, 30.44, 30.46, 30.48, 30.50, 30.52, 30.54, 30.56, 30.58, 30.60, 30.62, 30.64, 30.66, 30.68, 30.70, 30.72, 30.74, 30.76, 30.78, 30.80, 30.82, 30.84, 30.86, 30.88, 30.90, 30.92, 30.94, 30.96, 30.98, 31.00, 31.02, 31.04, 31.06, 31.08, 31.10, 31.12, 31.14, 31.16, 31.18, 31.20, 31.22, 31.24, 31.26, 31.28, 31.30, 31.32, 31.34, 31.36, 31.38, 31.40, 31.42, 31.44, 31.46, 31.48, 31.50, 31.52, 31.54, 31.56, 31.58, 31.60, 31.62, 31.64, 31.66, 31.68, 31.70, 31.72

[illegible]

OGGETTO:

MATERIALI UTILIZZATI

- CALCESTRUZZO (C25/30)
- ACCIAIO B450C

TRAVE
N°111
TAVOLA 3